



Compact 6000-count handheld clamp meter for accurate AC/DC current, voltage, resistance, and temperature measurement. Includes HOLD, NCV, buzzer, and diode test functions. Designed for professionals in industrial and field applications.

Measurement Ranges:

AC/DC Current	60 A / 600 A $\pm(2.0\% + 5)$, 0.01 A resolution
DC Voltage	600 mV / 6 / 60 / 600 V $\pm(0.5\% + 2)$, 0.1 mV res.
AC Voltage	6 / 60 / 600 V $\pm(0.8\% + 5)$, 0.001 V res.
Resistance	600 Ω to 60 M Ω $\pm(0.8\% + 2)$
Capacitance	60 nF to 60 mF $\pm(4.0\% + 5)$
Temperature	-40°C to 1000°C $\pm(2.5\% + 3)$
Frequency	10 Hz to 10 MHz $\pm(0.1\% + 4)$

Special Features:

Display	6000 counts
Clamp Size	Ø28 mm
Diode Test	1 mV
Continuity	Beeper < 10 Ω
Data Hold	Yes
NCV	EFHi / EFLo modes
Low Battery	Indicator < 2.6 V
Input Impedance	10 M Ω

Power & Environment:

Power	2 × 1.5V AAA batteries
Operating Temp.	0–40°C, <85% RH
Storage Temp.	-20–60°C, <75% RH
Altitude Limit	< 2000 m

Physical Specs:

Dimensions	485 × 320 × 385 mm
Weight	260 g
Accessories	Test leads, Temp probe, Batteries, Carry case, Manual