

TECPEL® TECPEL CO., LTD.

Digital AC/DC Amp Clamp meter DCM-2608D



(±Peak Hold) (TRUE RMS)
(Backlight)

- ❖ 6600 counts, bar graph display
- ❖ Dual Display of Frequency with Current or Voltage or % Duty Cycle
- ❖ Auto ranging
- ❖ Auto power off
- ❖ Overload protections
- ❖ Safety input jacks
- ❖ Safety test leads
- ❖ Safety: EN61010-1, EN 61010-2-032, CAT IV 600V, CAT III 1000V, CE approved
- ❖ Jaw opening capability: 57mm conductor.
- ❖ Dimensions: 281mm(H)×108mm(W)×53mm(D)
- ❖ Weight: Approx. 570g

SPECIFICATIONS

- ❖ DC Current: 660A, 2000A ±2.0%
- ❖ AC Current: 660A, 1500A ±2.0% (50-400Hz)
- ❖ DC Volts: 660mV, 6.6V, 66V, 660V, 1000V ±0.5%
- ❖ AC Volts: 660mV, 6.6V, 66V, 660V, 750V ±1.5% (50-500Hz)
- ❖ Resistance: 660Ω, 6.6kΩ, 66kΩ, 660kΩ, 6.6MΩ, 66MΩ ±1.0%
- ❖ Capacitance: 6.6nF, 66nF, 660nF, 6.6μF, 66μF, 660μF, 6.6mF ±3.0%
- ❖ % Ducus Cycle: 5% - 95% ±2.0%
- ❖ Frequency: 10Hz - 1MHz ±0.1%
- ❖ Diode Test
- ❖ Continuity Test
- ❖ DATA Hold
- ❖ MAX / MIN Hold
- ❖ Δ(Relative)
- ❖ DCA ZERO
- ❖ ±Peak Hold
- ❖ Backlight
- ❖ Resolution: 0.1A, 0.1mV, 0.1Ω, 1pF, 0.1%, 0.01Hz