

Automotive Multimeter



DMM-8088A

- ☆ 6600 counts, bar-graph, Dual display
- ☆ Auto ranging
- ☆ Auto power off
- ☆ Overload protections
- ☆ Safety input jacks
- ☆ Safety test leads
- ☆ Safety: EN61010-1, CAT IV 600V, CAT III 1000V, CE approved

SPECIFICATIONS

- ☆ RPM: 600 ~ 6600 (RPM), 6600 ~ 12000 (x10RPM) $\pm 2.0\%$
- ☆ Dwell angle: 4, 5, 6, 8 cylinders $\pm 2.0\%$
- ☆ ms pulse width: 0.1ms to 10ms $\pm 2.0\%$
- ☆ Duty cycle: 5% ~ 95% $>100\mu s$, $<100ms$ $\pm 2.0\%$
- ☆ DC Volts: 660mV, 6.6V, 66V, 660V, 1000V $\pm 0.5\%$
- ☆ AC Volts: 660mV, 6.6V, 66V, 660V, 750V $\pm 1.5\%$ (50~500Hz)
- ☆ DC Current: 660 μA , 6600 μA , 66mA, 400mA, 20A $\pm 1.0\%$
- ☆ AC Current: 660 μA , 6600 μA , 66mA, 400mA, 20A $\pm 1.5\%$ (50~500Hz)
- ☆ Resistance: 660 Ω , 6.6k Ω , 66k Ω , 660k Ω , 6.6M Ω , 66M Ω $\pm 1.0\%$
- ☆ Capacitance: 6.6nF, 66nF, 660nF, 6.6 μF , 66 μF , 660 μF , 6.6mF $\pm 3.0\%$
- ☆ Temperature: -20°C ~ 1000°C, -4°F ~ 1832°F $\pm 1.0\%$, K-type thermocouple
- ☆ Frequency: 10Hz~200kHz $\pm 0.1\%$
- ☆ Diode Test ☆ Continuity Test ☆ DATA Hold
- ☆ MAX / MIN Hold ☆ Δ (Relative) ☆ Backlight
- ☆ Resolution: 1RPM, 0.1mV, 0.1 μA , 0.1 Ω , 1pF, 0.01Hz, 0.1°C, 0.1°F
- ☆ Dimensions: 198mm(H)×90mm(W)×44mm(D)
- ☆ Weight: Approx. 400g

TECPEL CO.,LTD.

3F, No.12, Ln. 130, Minquan Rd., Xindian Dist.,
New Taipei City 23141, Taiwan
TEL:886-2-2218-3111 FAX:886-2-2218-3222
E-MAIL:tecpeelco@gmail.com



<http://www.tecpel.com>