

DCV, DCA, ACV, ACA, 4-20 mA, Temp.


PANEL METERS

Model : DR-99DCV, DR-99DCA

DR-99ACV, DR-99ACA

DR-99420, DR-99TEMP

ISO-9001, CE, IEC1010



LUTRON ELECTRONIC

The Art of Measurement

DCV, DCA, ACV, ACA, 4-20mA, Temp.

PANEL METERS

PANEL METER(DCV), 3 1/2 digits Model : DR99DCV	* 199.9 DCmV - 600 DCV, 5 ranges. * Range can be adjusted by jumper wire. * 110/220/230 ACV power, 14 mm red LED. * DIN size : 96 x 48 mm, Depth : 104 mm.
PANEL METER(DCA), 3 1/2 digits Model : DR99DCA	* 199.9 DC A - 10 DCA, 6 ranges. * Range can be adjusted by jumper wire. * 110/220/230 ACV power, 14 mm red LED. * DIN size : 96 x 48 mm, Depth : 104 mm.
PANEL METER(ACV), 3 1/2 digits Model : DR99ACV	* 199.9 ACmV - 600 ACV, 5 ranges. * Range can be adjusted by jumper wire. * 110/220/230 ACV power, 14 mm red LED. * DIN size : 96 x 48 mm, Depth : 104 mm.
PANEL METER(ACA), 3 1/2 digits Model : DR99ACA	* 199.9 AC A to 10 ACA, 6 ranges. * Range can be adjusted by jumper wire. * 110/220/230 ACV power, 14 mm red LED. * DIN size : 96 x 48 mm, Depth : 104 mm.
PANEL METER(4-20 mA), 3 1/2 digits Model : DR99420	* 4-20 mA, build "zero VR" & "gain VR", can match most kinds of transducers. * 110/220/230 ACV power, 14 mm red LED. * DIN size : 96 x 48 mm, Depth : 104 mm.
PANEL METER (TEMPERATURE) Model : DR99TEMP	* -50 °C to 1300 °C (x 0.1 °C, < 200 °C). * Jumper adjustment for oC/oF, 1 /0.1 . * 110/220/230 ACV power, 14 mm red LED. * DIN size : 96 x 48 mm, Depth : 104 mm.

* Appearance and specifications listed in this brochure are subject to change without notice.