

# TECPEL® TECPEL CO., LTD.

## Digital AC Amp Clamp meter DCM-2604D



( ±Peak Hold) (TRUE RMS)  
(Temperature) (Backlight)

- ❑ 6600 counts, bar graph display
- ❑ Dual Display of Frequency with Current or Voltage or % Duty Cycle
- ❑ Auto ranging
- ❑ Auto power off
- ❑ Overload protections
- ❑ Safety input jacks
- ❑ Safety test leads
- ❑ Safety: EN61010-1, EN 61010-2-032, CAT IV 600V, CAT III 1000V, CE approved
- ❑ Jaw opening capability: 51mm conductor.
- ❑ Dimensions: 279mm(H)×103mm(W)×53mm(D)
- ❑ Weight: Approx. 510g

### SPECIFICATIONS

- ❑ AC Current: 66A, 660A, 1000A ±2.0% (50-400Hz)
- ❑ DC Volts: 660mV, 6.6V, 66V, 660V, 1000V ±0.5%
- ❑ AC Volts: 660mV, 6.6V, 66V, 660V, 750V ±01.5%(50-500Hz)
- ❑ Resistance: 660Ω, 6.6kΩ, 66kΩ, 660kΩ, 6.6MΩ, 66MΩ ±1.0%
- ❑ Capacitance: 6.6nF, 66nF, 660nF, 6.6μF, 66μF, 660μF, 6.6mF ±3.0%
- ❑ Temperature: -35°C - 1000°C, -30°F - 1832°F ±1.0% K-type thermocouple
- ❑ % Duty Cycle: 5% - 95% ±2.0%
- ❑ Frequency: 10Hz - 1MHz ±0.1%
- ❑ Diode Test
- ❑ Continuity Test
- ❑ DATA Hold
- ❑ MAX / MIN Hold
- ❑ ±Peak Hold
- ❑ Backlight
- ❑ Resolution: 0.01A, 0.1mV, 0.1Ω, 1pF, 0.1°C, 0.1°F, 0.1%, 0.01Hz