

新上市



100KHz

LCR-2100

新上市



200KHz

LCR-2200



LCR 2000 系列為 6 位數顯示的桌上型 電容、電感、電阻量測儀。

可程控，使用彩色顯示面板，可顯示多種語言介面，一目了然的顯示介面，讓使用人員能快速上手。

可達 200KHz 的檢測訊號頻率，能測得最小 0.00001pF 數值，是檢測多種被動元件的最佳選擇。



數位控制面板



四輸入取樣端子


	LCR-2100	LCR-2200
顯示位數	999,999 顯示 (6位數顯示)	
訊號頻率	100K Hz(±0.05%)	200K Hz(±0.05%)
量測範圍	電容：9.99999 ~ 0.00001p F 電感：99.9999 ~ 0.00001u H 電阻：99.9999M ~ 0.00001Ω 頻率：99.9999 ~ 0.00001u S	
輸入訊號	電壓訊號 2 ~ 5mV ; 5m ~ 0.01mV 電流訊號 20m ~ 50uA ; 50u ~ 0.001uA	
分辨率	34 點	15,025 點
取樣速率	最快12.5ms	

取樣速度依照檢測的訊號頻率快慢有所區別。

泰菱有限公司

TEL: (02)2218-3111 FAX: (02)2218-3222 E-Mail: sales@oka.com.tw

Address: 23141 新北市新店區民權路130巷12號3樓





100KHz

LCR-2100



200KHz

LCR-2200



Adopting the new latest technology & high sophisticate circuit design and concentrating the essence of LCR test, TECPEL 2000 series is a new generation compact LCR meter of low cost and high performance.

Programmable and color display panel, multi-language interface, and the clearly display is easy operation for users . Detection signal frequency can measure up to 200KHz and down to the minimum of 0.00001pF, which is the best choice for detecting a variety of passive components.



Digital panel



Four terminal measurement

	LCR-2100	LCR-2200
Display	999,999 Counts	
Frequency	100K Hz(±0.05%)	200K Hz(±0.05%)
Range	Capacitance : 9.99999 ~ 0.00001p F Inductance : 99.9999 ~ 0.00001u H Resistance : 99.9999M ~ 0.00001Ω Frequency : 99.9999 ~ 0.00001u S	
Signal Input	Voltage 2 ~ 5mV ; 5m ~ 0.01mV Current 20m ~ 50uA ; 50u ~ 0.001uA	
Resolution	34 point	15,025 point
sampling	12.5ms	

* The sampling speed is different depending on the frequency of the detected signal.

